

## OPALE TOILET CUBICLE, 10 mm



Supply and layout of toilet partitions of the company SUFFIXE (70190 Rioz, phone : 03 84 91 24 70).

### Dimensions :

In function of the architect drawings

### In general :

- Doors, bearing wall and frontage mullion are created in 10 mm of solid grade laminate. It owns a soft completion. The panels are guaranteed to the humid atmosphere and have a fire classification (M2). The panels corner are bowed and polished.
- Cubicle height 1800 mm + minimum floor clearance 200 mm
- Following Suffixe grade laminate color chart, 20 colors are available

### Technical description :

- The bearing wall are freestanding in one part until a depth of 1,6m.
- The mullion are from the frontage bowed (in the bottom part). It avoid the big corner.
- The assembly parts (stirrup and angle bracket) are in stainless steel, gray varnished RAL 7040. It is fixed on the wall thanks to 4 angle bracket. The frontage mullion are gathered on the bearing wall thanks to 4 angle bracket.
- The mullions and the bearing wall are linked thanks by a mullion fitting to a girder and an aluminum frieze (which is covered of 100% polyester resin, oven-baked). It is in gray

varnished RAL7040. It is an exclusive assembly which do not need any support to be handled until 4,8m (mean 6 cubicle maximum). Above 6 cubicle, a support is needed.

- The adjustable feet are in glass fiber nylon. The feet is in varnished tube 50 x 50 mm. The colors is also gray RAL 7040.
- The fastenings are in stainless steel, with a specialized fingerprint system. (anti-theft system). It is invisible from the frontage. (option)
- The cubicle contains also a pivoting bolt in gray nylon (RAL 7040). A free/busy red and white indicator is added.
- 1 door indicator, in gray RAL 7040
- A gray (RAL 7040 ) multifunctional split hinge is provided. 2 split hinge per doors. It is manufactured in fiberglass nylon.

### **Options / accessories:**

- A shower partition + bench ( $\frac{1}{4}$  rounded of rectangular).
- Shower panels with pipework. Colors in function of Suffixe grade laminate color chart.
- Pictogram can be written (men, women, people with reduced mobility toilet...)
- Stainless steel double hook (gray, RAL 7040)
- toilet sheet of paper distributor, also in nylon RAL 7040 or in stainless steel with a lock.
- Lift bar destined for disabled people, in gray nylon RAL 7040
- Soap dish in gray nylon RAL 7040



## OPALE TOILET CUBICLE, 13 mm

Supply and layout of toilet partitions of the company SUFFIXE (70190 Rioz, phone : 03 84 91 24 70).

### Dimensions :

In function of the architect drawings

### In general :

- Doors, bearing wall and frontage mullion are created in 13 mm of solid grade laminate. It owns a soft completion. The panels are guaranteed to the humid atmosphere and have a fire classification (M2). The panels corner are bowed and polished.
- Cubicle height 1800 mm + minimum floor clearance 200 mm
- Following Suffixe grade laminate color chart, 20 colors are available

### Technical description :

- The bearing wall are freestanding in one part until a depth of 1,6m.
- The mullion are from the frontage bowed (in the bottom part). It avoid the big corner.
- The assembly parts (stirrup and angle bracket) are in stainless steel, gray varnished RAL 7040. It is fixed on the wall thanks to 4 angle bracket. The frontage mullion are gathered on the bearing wall thanks to 4 angle bracket.
- The mullions and the bearing wall are linked thanks by a mullion fitting to a girder and an aluminum frieze (which is covered of 100% polyester resin, oven-baked). It is in gray varnished RAL7040. It is an exclusive assembly which do not need any support to be handled until 4,8m (mean 6 cubicle maximum). Above 6 cubicle, a support is needed.
- The adjustable feet are in glass fiber nylon. The feet is in varnished tube 50 x 50 mm. The colors is also gray RAL 7040.
- The fastenings are in stainless steel, with a specialized fingerprint system. (anti-theft system). It is invisible from the frontage. (option)
- The cubicle contains also a pivoting bolt in gray nylon (RAL 7040). A free/busy red and

white indicator is added.

- 1 door indicator, in gray RAL 7040
- A gray (RAL 7040 ) multifunctional split hinge is provided. 2 split hinge per doors. It is manufactured in fiberglass nylon.

### **Options / accessories:**

- A shower partition + bench ( $\frac{1}{4}$  rounded of rectangular).
- Shower panels with pipework. Colors in function of Suffixe grade laminate color chart.
- Pictogram can be written (men, women, people with reduced mobility toilet...)
- Stainless steel double hook (gray, RAL 7040)
- toilet sheet of paper distributor, also in nylon RAL 7040 or in stainless steel with a lock.
- Lift bar destined for disabled people, in gray nylon RAL 7040
- Soap dish in gray nylon RAL 7040